

PROKTES

Metal Frame Metal Mesh Kitchen Hood Filter | Panel Filter



Filter Media	Aluminium	
Frame Material	Galvanized Steel	
Average Gravimetric Efficiency	65-80 %	80-90 %
Classification (EN 779:2002)	G2	G3
Eurovent Class	EU2	EU3
Initial Pressure Drop	10-25	30
Final Pressure Drop	450 Pa	450 Pa
Max. Temperature	100 °C	100 °C
Max. Moisture	100 %	100 %

Product Code	Dimensions (WxHxD)	Media Area (m ²)	Air Flow (m ³ /h)	Press. Drop (Pa)	Weight (Kg)
12-G2					
MKF-GAL-287/287/12-G2	287x287x12	0,18	600	10	1,2
MKF-GAL-400/500/12-G2	400x500x12	0,39	1440	10	1,65
MKF-GAL-500/500/12-G2	500x500x12	0,47	1800	10	1,95
MKF-GAL-500/625/12-G2	500x625x12	0,61	2250	10	2,2
MKF-GAL-287/592/12-G2	287x592x12	0,35	1225	10	1,65
MKF-GAL-490/592/12-G2	490x592x12	0,52	2090	10	2,1
MKF-GAL-592/592/12-G2	592x592x12	0,68	2525	10	2,4
24-G2					
MKF-GAZ-287/287/24-G2	287x287x24	0,2	600	20	1,4
MKF-GAZ-400/500/24-G2	400x500x24	0,45	1440	20	1,92
MKF-GAZ-500/500/24-G2	500x500x24	0,55	1800	20	2,25
MKF-GAZ-500/625/24-G2	500x625x24	0,7	2250	20	2,65
MKF-GAZ-287/592/24-G2	287x592x24	0,42	1225	20	1,95
MKF-GAZ-490/592/24-G2	490x592x24	0,65	2090	20	2,45
MKF-GAZ-592/592/24-G2	592x592x24	0,8	2525	20	2,8
48-G2					
MKF-GAZ-287/287/48-G2	287x287x48	0,29	600	25	2
MKF-GAZ-400/500/48-G2	400x500x48	0,65	1440	25	3,4
MKF-GAZ-500/500/48-G2	500x500x48	0,85	1800	25	3,9
MKF-GAZ-500/625/48-G2	500x625x48	0,1	2250	25	4
MKF-GAZ-287/592/48-G2	287x592x48	0,6	1225	25	3,2
MKF-GAZ-490/592/48-G2	490x592x48	0,98	2090	25	3,9
MKF-GAZ-592/592/48-G2	592x592x48	1,2	2525	25	4,5

Advantages

- Economic Operation and high filtration surface
- Available at Galvanized, Aluminum and Stainless Steel Frame and media
- Low pressure drop
- High oil and oil smoke holding capacity
- Totally washable and reusable
- Available at out of standart size

